

NEW Series

THETIS 7003

CHAIN COUNTER



Radio Control Chain counter THETIS 7003

Without cable ties, plug or panels and with load always perfect by rechargeable battery, the radio chain counter **THETIS 7003** gives finally all the **freedom of manoeuvres** and the **comfort of reading** in the anchoring operations.

Reinforced covers & buttons.

- ✓ Chain speed indicator / mooring length in meters or feet
- ✓ Voltage indicator
- ✓ Up alarm sensor
- ✓ Switch on button / Key tones adjustment
- ✓ High vision LCD display / Backlit display screen / Eight level of contrast
- ✓ Six language menu (IT, EN, FR, DE, ES, GR)
- ✓ Able to control free fall windlasses
- ✓ Parallel connection
- ✓ USB cable and charger included
- ✓ Cradle included

| Code | 73633 |
|---------------------------|-----------------------------------|
| Command transmission | Remote |
| Number of buttons | 3 (Transmitter) |
| Voltage | 12 - 24V _{dc} (Receiver) |
| Operative temperature | -10 : +60 |
| IP protection rated* | 67 (Transmitter)** |
| Max contacts amperage (A) | 2 (Receiver) |
| Weight (gr) | 480 |
| Dimension (mm) | 154x59x38 (Transmitter) |

**Excluding cable connection zone

THETIS 5003

CHAIN COUNTER



Hand Held Remote Control Chain counter THETIS 5003

This remote chain counter model **THETIS 5003** has been specifically designed to give the **full control in anchoring**. It's a reliable and practical instrument, technologically advanced, specifically design for use in marine environments. The external casing, rated with **IP66** and supplied with **waterproof plug** and **socket rated IP67**. The extending flexible cable (approximately 4 metres) gives the **maximum freedom** on board during anchoring manoeuvring. Provided with an evolved microprocessor that offers a series of advantages for **full control of the anchoring**.

Reinforced covers & buttons.

- ✓ Chain speed indicator / mooring length in meters or feet
- ✓ Voltage indicator
- ✓ Up alarm sensor
- ✓ Switch on button / Key tones adjustment
- ✓ High vision LCD display / Backlit display screen / Eight level of contrast
- ✓ Six language menu (IT, EN, FR, DE, ES, GR)
- ✓ Able to control free fall windlasses
- ✓ Parallel connection
- ✓ Cradle included

| Code | 73632 |
|---------------------------|------------------------|
| Command transmission | Wire |
| Number of buttons | 3 |
| Voltage | 12 - 24V _{dc} |
| Operative temperature | -10 : +60 |
| IP protection rated* | 67 |
| Max contacts amperage (A) | 2 |
| Weight (gr) | 710 |
| Dimension (mm) | 154x59x38 |

*Excluding cable connection zone (IP68: plug & socket)

NEW Series

THETIS 1002

HAND HELD CONTROL



Cradle

Hand Held Control THETIS 1002

This hand held remote control model **THETIS 1002** has an **elegant and functional design**. The soft rubber case, which covers sideways the remote control, **allows a safe and handy taking under any condition**.

This hand held remote control is rated with **IP66** and supplied with **waterproof plug** and **socket rated IP67**. The extending flexible cable (approximately 4 metres) gives the **maximum freedom** on board during anchoring manoeuvring.

Reinforced covers & buttons.

- ✓ Inversion polarity protection
- ✓ Parallel connection
- ✓ 2 buttons (up-down)
- ✓ Cradle included

| Code | 73631 |
|---------------------------|------------------------|
| Command transmission | Wire |
| Number of buttons | 2 |
| Voltage | 12 - 24V _{dc} |
| Operative temperature | -10 : +60 |
| IP protection rated | 67 |
| Max contacts amperage (A) | 2 |
| Weight (gr) | 580 |
| Dimension (mm) | 154x59x38 |

IRIS II

CHAIN COUNTER



Panel Chain counter IRIS II

This fly bridge chain counter **IRIS II** is technologically advanced instrument with an **elegant and ergonomic design** makes it suitable for all type of boat cockpits.

IRIS II is supplied with an evolved microprocessor, with different operations **allowing an optimum anchoring**.

New larger display.

- ✓ Chain speed indicator / mooring length in meters or feet
- ✓ Voltage indicator
- ✓ Up alarm sensor
- ✓ Switch on button / Key tones adjustment
- ✓ High vision LCD display 3,3" / Backlit display screen / Eight level of contrast
- ✓ Six language menu (IT, EN, FR, DE, ES, GR)
- ✓ Able to control free fall windlasses
- ✓ Parallel connection

| Code | 600017 |
|---------------------------|------------------------|
| Command transmission | Wire |
| Number of buttons | 3 |
| Voltage | 12 - 24V _{dc} |
| Operative temperature | -10 : +60 |
| IP protection rated* | 67 |
| Max contacts amperage (A) | 2 |
| Weight (gr) | 500 |
| Dimension (mm) | 110x105x15** |

* When installed **Recessed option