

LENCO ELECTRIC HATCH LIFTS

PRODUCT INFORMATION DOWNLOAD



file shown
20760-001 through 20789-001.



Electric Hatch Lifts 12 & 24-Volt Models

12 and 24-Volt with 2' leads & deutsch connectors. Inline motor design delivers over 500 lbs. of force. Includes vandar mounting brackets & stainless steel pull pins.

Hatch Lift Features:

- ▶ NEW - Clear anodized aluminum tubing
- ▶ Sizes available with 4" thru 30" stroke. Available in 12- and 24-volt
- ▶ Complete with 2' lead and Deutsch plug (actuator extension harnesses are available in lengths of 7', 14', 20', 26', 32' and 45')
- ▶ Clutchless ball screw design will not drift, never binds and runs in sync on dual lift applications
- ▶ Inline motor design delivers over 500 lbs. (226.79 Kg) of force
- ▶ Water resistant, made entirely of non corrosive materials
- ▶ Ball screw spins freely when hatch is fully opened or closed eliminating limit switches and burned out motors
- ▶ Vandar mounting brackets with stainless steel pull pins
- ▶ Powdered metal gears for strength and precision
- ▶ Stainless steel ram locks in any position
- ▶ Amp draw 10 amps at 12-volt and 5 amps at 24-volt
- ▶ CE-certified and ABYC compliant
- ▶ O-ring sealed at 100 psi

SWITCH KITS SOLD SEPARATELY



Single Rocker Switch for hatch lifts with two 30" non-terminated power leads.

- 15096-001 Single hatch lift applications
- 15098-001 Twin hatch lift applications

Electric Hatch Lifts with 2' Leads and Deutsch connectors

L.O.A. = Length Overall, measuring from top bracket to bottom bracket


12-Volt Models

| Lenco Part# | Superseded Part# | L.O.A. Retracted | Approximate Stroke | L.O.A. Extended |
|-------------|------------------|------------------|--------------------|-----------------|
| 20760-001 | HL-400 | 15" | 4" | 19" |
| 20762-001 | HL-600 | 20" | 6" | 26" |
| 20764-001 | HL-800S | 20" | 8" | 28" |
| 20766-001 | HL-800 | 24" | 8" | 32" |
| 20768-001 | HL-1200S | 24" | 12" | 36" |
| 20770-001 | HL-1200 | 29" | 12" | 41" |
| 20774-001 | HL-1600S | 29" | 16" | 45" |
| 20776-001 | HL-1600 | 33" | 16" | 49" |
| 20778-001 | HL-2000S | 33" | 20" | 53" |
| 20780-001 | HL-2000 | 37" | 20" | 57" |
| 20782-001 | HL-2400S | 37" | 24" | 61" |
| 20784-001 | HL-2400 | 41" | 24" | 65" |
| 20786-001 | HL-2600 | 47" | 26" | 73" |
| 20788-001 | HL-3000 | 47" | 30" | 77" |

24-Volt Models

| | | | | |
|-----------|--------------|-----|-----|-----|
| 20761-001 | HL-400/24V | 15" | 4" | 19" |
| 20763-001 | HL-600/24V | 20" | 6" | 26" |
| 20765-001 | HL-800S/24V | 20" | 8" | 28" |
| 20767-001 | HL-800/24V | 24" | 8" | 32" |
| 20769-001 | HL-1200S/24V | 24" | 12" | 36" |
| 20771-001 | HL-1200/24V | 29" | 12" | 41" |
| 20775-001 | HL-1600S/24V | 29" | 16" | 45" |
| 20777-001 | HL-1600/24V | 33" | 16" | 49" |
| 20779-001 | HL-2000S/24V | 33" | 20" | 53" |
| 20781-001 | HL-2000/24V | 37" | 20" | 57" |
| 20783-001 | HL-2400S/24V | 37" | 24" | 61" |
| 20785-001 | HL-2400/24V | 41" | 24" | 65" |
| 20787-001 | HL-2600/24V | 47" | 26" | 73" |
| 20789-001 | HL-3000/24V | 47" | 30" | 77" |

OPTIONAL HATCH LIFT ACCESSORIES AVAILABLE



Optional stainless steel non-locking slide bracket for hatch lifts
70381-001

In case of power failure, this bracket allows you to pull the hatch open 4" in order to remove pull pin for access.